

**Vertical Mast Lift** 

**HM0608E** 

**GB/CE/ANSI** Compliance

## **HIGH LIGHTS**

- Electric drive, zero emission, energy-saving and environmentally friendly.
- Accurate control and smooth driving.
- Simple design and easy maintenance.
- The two sides of the rotating tray are convenient for maintenance services.
- High precision platform overload sensing system reduces accidental false alarms and shutdowns.

## **FEATURES**

## **Standard**

Self-lock Gate
Pothole Guard System
Automatic Braking System
Motion Alarm
Emergency Decent System
Full Height Drive
Emergency Stop Button
Flashing Beacons

Overload Sensing System
AC Power to the Platform
Fault Diagnosis System
One-Way Extension Platform
Tilt Protection System
Charging Protection System
Forklift Hole

Grand in Sound
Sharp in Heart
Viture in Action



## Vertical Mast Lift

**HM0608E** 

**GB/CE/ANSI** Compliance

| Model                          | HM0608E        |
|--------------------------------|----------------|
| Measurements                   |                |
| Max. Working Height            | 7.7m           |
| A-Max. Platform Height         | 5.7m           |
| B-Platform Length              | 1.5m           |
| C-Platform Width               | 0.78m          |
| Extension Size                 | 0.5m           |
| D-Height (Rails Up)            | 1.99m          |
| E-Length (with Ladder)         | 1.62m          |
| F-Overall Width                | 0.8m           |
| G-Wheel Base                   | 1.28m          |
| H-Clearance (Stowed)           | 0.08m          |
| I-Clearance (Raised)           | 0.02m          |
| Performanc                     | e              |
| Platform Capacity              | 200kg          |
| Extension Capacity             | 113kg          |
| Max. Occupancy(indoor/outdoor) | 1/0            |
| Drive Speed (Stowed)           | 3.5km/h        |
| Drive Speed (Raised)           | 0.6km/h        |
| Turning Radius (In.)           | 0.6m           |
| Turning Radius (Out.)          | 1.8m           |
| Up/Down Time                   | 32/32s         |
| Gradeability                   | 25%            |
| Max. Slope                     | 1.5°/3°        |
| Drive                          | Double-Rear    |
| Tires (mm)                     | 305×100mm      |
| Power                          |                |
| Batteries(V/Ah)                | 2×12V/100Ah    |
| Charger                        | 100-240VAC/15A |
| Weight                         |                |







