

HS1623RT

HIGHLIGHTS

Strong off-road performance.
Rough terrain tyre, large ground clearance,
stronger passability.
Engine drive, more powerful.

Configurations Standard

Automatic Braking	Platform Self-lock Door
Proportional Control	Self-diagnosis
Emergency Descent	Flashing Beacons
Emergency Stop	Tilt Sensor
Extension Platform	Safety Arm
Folding Guardrails	Outriggers
Motion Alarm	Horn
Hour Meter	

Optional

Working Lamp on the Platform
Load Sensing System
AC Power to the Platform
Air Pipe to the Platform

HS1218ERT

HIGHLIGHTS

Drive on all rough terrains.
Large ground clearance, stronger passability.
AC motor drive, smooth driving, low noise.
Large capacity batteries, better endurance.

Configurations Standard



Automatic Braking	Self-diagnosis
Proportional Control	Charging Protection
Emergency Descent	Flashing Beacons
Hour Meter	Tilt Sensor
Motion Alarm	Safety Arm
Emergency Stop	Platform Self-lock Door
Extension Platform	Horn
Folding Guardrails	

Optional


Working Lamp on the Platform
Load Sensing System
AC Power to the Platform
Air Pipe to the Platform
Outriggers

Self-propelled Rough Terrain Scissor Lifts

MOBILE ELEVATING WORK PLATFORMS



Models	HS1623RT
Measurements	
Max. Working Height	17.95m
A-Max. Platform Height	15.95m
Platform Dimension (B×C)	3.81x1.83m
Front Platform Extension Length	1.536m
Rear Platform Extension Length	1.231m
D-Overall Height (Rails Up)	3.21m
Overall Height (Rails Folded)	2.44m
E-Overall Length (with Ladder)	4.88m
Overall Width with Outriggers	2.29m
G-Ground Clearance	260mm
F-Wheel Base	2862mm
Performance	
Platform Capacity	680kg
Extension Capacity	230kg
Max. Occupancy(indoor/outdoor)	4/4
Drive Height	8.5m
Drive Speed (Stowed)	6.1km/h
Drive Speed (Raised)	1.1km/h
Up/Down Time	55/65s
Turning Radius (Out.)	3.9m
Tilt Rating (Front to Rear/Side to Side)	3°/2°
Gradeability	40%
Max Outrigger Leveling (Front to Rear)	7°
Max Outrigger Leveling (Side to Side)	12°
Max. Wind Speed	12.5m/s
Tires	
Tire Size	832x290mm
Power	
Hydraulic Oil Tank Capacity	120L
Fuel Tank Capacity	120L
Engine	Kubota V2403
Drive Type	4WD
Weight	
Weight	7980kg



Models	HS1218ERT
Measurements	
Max. Working Height	14m
A-Max. Platform Height	12m
B-Platform Length	2.92m
C-Platform Width	1.65m
Extension Size	0.65m(Double side)
D-Overall Height (Rails Up)	2.88m
Overall Height (Rails Folded)	2.10m
E-Overall Length (with Ladder)	3.75m
F-Overall Width	1.75m
G-Wheel Base	2300mm
H-Ground Clearance	200mm
Performance	
Platform Capacity	360kg
Extension Capacity	113kg
Max. Occupancy(indoor/outdoor)	3/2
Drive Speed (Stowed)	4.8km/h
Drive Speed (Raised)	0.6km/h
Turning Radius(In.)	2.29m
Turning Radius (Out.)	4.88m
Up/Down Time	54/50s
Gradeability	45%
Max. Slope	2°/3°
Control	Proportional Control
Drive	Four-Wheel
Multi Disc Brake	Four-Wheel
Tire Size	26x12-16
Max. Wind Speed	12.5m/s
Power	
Batteries (V/Ah)	8×6V/370Ah
Charger	100-240VAC/35A
Weight	
Weight	5600kg