

# HERED®

## Articulating Boom Lift

### HA19J

GB/CE/ANSI Compliance



## HIGHLIGHTS

- Flexible movement, capable of achieving composite boom movements, with a wide range of operations.
- Four-wheel drive, floating axle design, better passability.
- Integrated rotary reducer makes smooth turning, comprehensive protection can adapt to dust environment.
- High-precision overload sensing system to reduce accidental false alarms and shutdowns.

## FEATURES

### Standard

Horn  
Proportional controls  
Motion Alarm  
Flashing Beacons  
Self-lock Gate  
Emergency Descent System  
Emergency Stop System  
Automatic Leveling Platform  
Fault Diagnosis System  
Overload Sensing System  
Tilt Protection System  
Oscillating axle  
Released Type Engine Tray  
Color Display

### Optional

AC power to the platform  
Air tube to the platform

*Grand in Sound  
Sharp in Heart  
Viture in Action*

[sales@hrdlift.com](mailto:sales@hrdlift.com)

[www.hered-lift.com](http://www.hered-lift.com)

# HERED®

## Articulating Boom Lift

# HA19J

GB/CE/ANSI Compliance

Models	HA19J
<b>Measurements</b>	
Max. Working Height	20.77m
Max. Platform Height	18.77m
Max. Horizontal Extension	12m
Max. Up and Over	8.1m
A-Length (Stowed)	9.0m
B-Width (Stowed)	2.49m
C-Height (Stowed)	2.697m
D-Platform Length	2.4m
E-Platform Width	0.9m
F-Wheelbase	2.5m
G-Ground Clearance	0.31m
<b>Performance</b>	
Platform Capacity	250kg
Max. Drive Speed (Stowed)	4.8km/h
Max. Gradeability (Stowed)	45%
Turning Radius (In.)	2.42m
Turning Radius (Out.)	5.57m
Turntable Rotation	360° Continuous
Platform Rotation	±90°
H-Turntable Tailswing	0
Tilt Rating	5°
Operating Wind Speed	12.5m/s
<b>Power</b>	
Engine	Kubota V2403
Power	36.5kw
<b>Tires</b>	
Tires	355/55D625
<b>Weight</b>	
Weight	11000kg
Hydraulic Tank Capacity	130L
Fuel Tank Capacity	120L

