

HERED®

Self-Propelled Scissor Lifts

H series

GB/CE/ANSI Compliance

HIGHLIGHTS

Flexible and Stable

- Optimized matching, high cycle times, better endurance.
- Precise control greatly improves the smoothness of operating.
- Large ground clearance, stronger passability.

Lower TCO

Universal and modular design, easy maintenance.

Swing out trays of batteries and hydraulic system.

Durable, stable and safe.

FEATURES

Standard

Self-lock Gate

Pothole Guard

Proportional Controls

Automatic Braking System

Motion Alarm

Emergency Decent

Full Height Drive

Folding Guardrails

Emergency Stop

Hourmeter

Flashing Beacon

Self-diagnosis

Extension Platform

Safety Arm

Tilt Sensor

Charging Protection

Forklift Hole

Horn

Optional

Load Sensing System

AC Power to the Platform

Air Tube to the Platform



*Grand in Sound
Sharp in Heart
Viture in Action*

HERED®

Self-Propelled Scissor Lifts

H series

GB/CE/ANSI Compliance

Models	HS0607H	HS0608H	HS0808H	HS0812H	HS1012H	HS1212H	HS1413H
Measurements							
Max.Working Height	7.8m	7.9m	9.9m	9.8m	11.8m	13.8m	15.7m
A-Max. Platform Height	5.8m	5.9m	7.9m	7.8m	9.8m	11.8m	13.7m
B-Platform Length	1.63m	2.26m	2.26m	2.26m	2.26m	2.26m	2.64m
C-Platform Width	0.74m	0.81m	0.81m	1.12m	1.12m	1.12m	1.12m
Extension Size	0.9m	0.9m	0.9m	0.9m	0.9m	0.9m	0.9m
D-Height(Rails Up)	2.17m	2.15m	2.27m	2.28m	2.51m	2.62m	2.62m
Height(Rails Down)	1.83m	1.84m	1.96m	1.68m	1.96m	2.09m	2.1m
E-Length(With Ladder)	1.86m	2.43m	2.43m	2.49m	2.49m	2.49m	2.84m
F-Overall Width	0.76m	0.81m	0.81m	1.18m	1.18m	1.19m	1.25m
G-Wheelbase	1.32m	1.87m	1.87m	1.87m	1.87m	1.87m	2.22m
H-Clearance(Stowed)	0.06m	0.1m	0.1m	0.1m	0.1m	0.1m	0.1m
I-Clearance(Raised)	0.02m	0.02m	0.02m	0.02m	0.02m	0.02m	0.02m
Performance							
Platform Capacity	230kg	380kg	230kg	450kg	320kg	320kg	250kg
Extension Capacity	113kg	113kg	113kg	113kg	113kg	113kg	113kg
Max.Occupancy	2	2	2	2	2	2	2
Drive Speed(Stowed)	4km/h	3.5km/h	3.5km/h	3.5km/h	3.5km/h	3.5km/h	3.5km/h
Drive Speed(Raised)	0.8km/h	0.8km/h	0.8km/h	0.8km/h	0.8km/h	0.8km/h	0.8km/h
Turning Radius(in.)	0m	0m	0m	0m	0m	0m	0m
Turning Radius(out.)	1.55m	2.1m	2.1m	2.3m	2.3m	2.3m	2.3m
Up/Down Time	16/34(s)	30/34(s)	31/40(s)	35/40(s)	62/39(s)	65/60(s)	80/60(s)
Gradeability	25%	30%	25%	25%	25%	25%	25%
Tilt Rating	1.5°/3°	1.5°/3°	2°/3°	2°/3°	1.5°/3°	1.5°/3°	1.5°/3°
Control	Proportional	Proportional	Proportional	Proportional	Proportional	Proportional	Proportional
Drive	FWD	FWD	FWD	FWD	FWD	FWD	FWD
Multi Disc Brake	Rear	Rear	Rear	Rear	Rear	Rear	Rear
Tires	305mmx100mm	381mmx127mm	381mmx127mm	381mmx127mm	381mmx127mm	381mmx127mm	381mmx127mm
Power							
Batteries	4X6V/200Ah	4X6V/200Ah	4X6V/200Ah	4X6V/200Ah	4X6V/200Ah	4X12V/200Ah	4X12V/200Ah
Charger	100-240VAC/30A	100-240VAC/30A	100-240VAC/30A	100-240VAC/30A	100-240VAC/30A	100-240VAC/30A	100-240VAC/30A
Weight							
Weight	1560kg	1985kg	2240kg	2620kg	2800kg	3020kg	3300kg

