

HIGHLIGHTS

- AC motor drive, smooth driving, better micro mobility.
- High-precision overload sensing system to reduce accidental and false alarm shutdown.
- Integrated rotary reducer makes smooth turning, comprehensive protection can adapt to dust environment.
- Large capacity batteries, strong endurance.

FEATURES

Proportional controls

Emergency Descent System Emergency Stop System Automatic Leveling Platform Fault Diagnosis System Overload Sensing System

Standard

Motion Alarm Flashing Beacons Self-lock Gate

Horn

Optional

AC power to the platform Air tube to the platform

Grand in Sound Sharp in Heart Viture in Action

sales@hrdlift.com

www.hered-lift.com



Models	HA14JE
Measurements	
Max. Working Height	15.7m
Max. Platform Height	13.7m
Max. Horizontal Extension	7.24m
Max.Up and Over Height	7.7m
A- Length (Stowed)	6.42m
B- Width (Stowed)	1.75m
C- Height (Stowed)	2.01m
D- Platform Length	1.52m
E- Platform Width	0.76m
F- Wheelbase	2.01m
G- Ground Clearance	0.2m
Performance	
Platform Capacity	230kg
Max.Drive Speed (Stowed)	5.2km/h
Max.Gradeability (Stowed)	30%
Turning Radius (In.)	0.8m
Turning Radius (Out.)	3.8m
Turntable Rotation	355°
Platform Rotation	±90°
H- Turntable Tailswing	0
Tilt Rating	3°
Operating Wind Speed	12.5m/s
Power	
Batteries(V/Ah)	8x6V/370Ah
Charger	48V/35A
	ires
Tires	240/55—17.5
Weight	
Weight	7070kg
Hydraulic Tank Capacity	20L





