

HERED®

Telescopic Boom Lift

HT20J

GB/CE/ANSI Compliance

HIGHLIGHTS

- Quick action response and large operation radius.
- Fault self-diagnosis system.
- The industry's leading platform capacity with dual load capacity of 300kg / 450kg.
- Smooth telescopic boom control technology.
- Floating design, high passability and off-road capability.

FEATURES

Standard

Automatic Leveling Platform
Horn
Self-fault diagnosis System
Proportional Control
Tilt Sensor
Motion Alarm
Swing Bridge

Flashing Beacons
Load Sensing System
Self-lock Gate
Color Display
Emergency Decent System
Swing-out Engine Tray
Emergency Stop System

Optional

AC Power to the Platform

*Grand in Sound
Sharp in Heart
Viture in Action*

sales@hrdlift.com

www.hered-lift.com



HERED®

Telescopic Boom Lift HT20J

GB/CE/ANSI Compliance

Model	HT20J
Measurements	
Max. Working Height	21.8m
Max. Platform Height	19.8m
Max. Horizontal Extension	16.6m
A- Length (Stowed)	9.76m
B- Width (Stowed)	2.49m
C-Height(Stowed)	2.77m
D- Platform Length	2.44m
E- Platform Width	0.91m
F- WheelBase	2.5m
Wheel Track	2.1m
G- Ground Clearance	0.31m
Performance	
Max.Capacity(Unrestricted/Restrictend)	300kg/450kg
Max.Drive Speed (Stowed)	4.8km/h
Max.Gradeability	45%
Turning Radius (In.)	2.42m
Turning Radius (Out.)	5.57m
Turntable Rotation	Continuous 360°
Platform Rotation	-80°— 80°
Jib Swing Angle	-65°— 78°
Tilt Rating	5°
Max.Operating Wind Speed	12.5m/s
Turntable Tail Swing	1.42m
Power	
Power Source	Kubota V2403
Fuel Tank Capacity	130L
Control	12V
Hydraulic Tank Capacity	170L
Drive	AWD
Steering	Front Wheels
Tires	
Tires	355/55D 625—16
Weight	
Weight	12100kg

