

# HERED®

## Self-Propelled Rough Terrain Scissor Lift

# HS1623RT

GB/CE/ANSI Compliance

## HIGH LIGHTS

- Strong off-road performance.
- Rough terrain tyre, large ground clearance, strong passing ability.
- Engine drives, more powerful.

## FEATURES

### Standard

Automatic Braking	Emergency Stop	Flashing Beacons
Proportional Control	Extension Platform	Tilt Sensor
Emergency Descent	Folding Guardrails	Safety Arm
Hour Meter	Self-diagnosis	Self-lock gate
Motion Alarm	Horn	Charging Protection
		Outrigger

### Optional

Working Lamp on the Platform  
Load Sensing System  
AC Power to the Platform  
Air Pipe to the Platform



*Grand in Sound  
Sharp in Heart  
Viture in Action*

sales@hrdlift.com

www.hered-lift.com

# HERED®

## Self-Propelled Rough Terrain Scissor Lift

# HS1623RT

GB/CE/ANSI Compliance

Models	HS1623RT
<b>Measurements</b>	
Max. Working Height	17.95m
A-Max. Platform Height	15.95m
Platform Dimension (B×C)	3.81×1.83m
Front Platform Extension Length	1.536m
Rear Platform Extension Length	1.231m
D-Overall Heights (Rails Up)	3.21m
Overall Height (Rails Folded)	2.44m
E-Overall Length (with Ladder)	4.88m
Overall Width with Outriggers	2.29m
F-Wheelbase	2862mm
G-Ground Clearance	260mm
<b>Performance</b>	
Platform Capacity	680kg
Extension Capacity	230kg
Max. Occupancy	4Persons
Drive Height	8.5m
Drive Speed (Stowed)	6.1km/h
Drive Speed (Raised)	1.1km/h
Up/Down Time	55/65s
Turning Radius (Out.)	3.9m
Tilt Rating (Front to Rear/Side to Side)	3°/2°
Gradeability	40%
Max Outrigger Leveling (Front to Rear)	7°
Max Outrigger Leveling (Side to Side)	12°
<b>Tires</b>	
Tires Size (mm)	832×290mm
<b>Power</b>	
Hydraulic Oil Tank Capacity	120L
Fuel Tank Capacity	120L
Engine	KubotaV2403
Drive Type	4WD×2WS
<b>Weight</b>	
Weight	7980kg

